

No

P081-4

version: 1

1 Unique identification code of the product-type: **Icopal P Base 35 ww Speed Profile SBS - typ T**

2 Intended use/es:

- a. damp proofing for buildings, including basement tanking
- b. damp proofing for buildings, including basement tanking subject to reaction to fire

3 Manufacturer:

Icopal Sp. z o.o., ul. Łaska 169/197,
98-220 Zduńska Wola, Polska (PL)

4 System/s of AVCP:

System 2+, System 3

5 Harmonised standard:

EN 13969:2004+A1:2006

Notified body/ies:

The notified factory production control certification body No. 1434:
POLSKIE CENTRUM BADAŃ I CERTYFIKACJI S.A.
(system 2+, scope of application a.)

The notified testing laboratory No. 1434:
POLSKIE CENTRUM BADAŃ I CERTYFIKACJI S.A.
(system 3, scope of application b.)

6 Declared performance/s:

Essential characteristics	Performances
Reaction to fire	Class E
Watertightness	60 kPa
Resistance to impact, method A	500 mm
Resistance to impact, method B	900 mm
Shear resistance of joints, side lap	500 ± 200 N/50 mm
Shear resistance of joints, end lap	600 ± 200 N/50 mm
Flexibility at low temperatures (pliability)	-15 °C
Tensile strength longitudinal	750 ± 250 N/50 mm
Tensile strength transverse	550 ± 200 N/50 mm
Elongation longitudinal	45 ± 15 %
Elongation transverse	45 ± 15 %
Resistance to static load, method B	15 kg
Resistance to tearing longitudinal	275 ± 50 N
Resistance to tearing transverse	275 ± 50 N
Durability against artificial ageing/degradation: watertightness	60 kPa
Durability against chemicals: watertightness	NPD
Dangerous substances	not contain

NPD - No performance determined

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

At Zduńska Wola on 24th January 2018

CZŁONEK ZARZĄDU
DYREKTOR
DS. TECHNICZNO PRODUKCYJNYCH
Grzegorz Hese